

## Supplemental Information & Instructions for 222-211 Seat Belt, Competition



These belts are suitable for installation in virtually any British Sports car. Save for a small change in dimensions, the design of the quick release buckle has remain unchanged since the 1950's. The manufacturer of the buckles went from a 3 inch wide design to the current 2.5 inch wide design in 1999. The mounting eye-bolts are 7/16" UNF. Each belt is a maximum of 29 inches long, measured from the center of the snap hook to the engaged part of the buckle.

### **Installation Tips**

When available, be sure to use the vehicle manufacturer's provisions to attach belts. When you use the manufacturer's threaded floor fittings, it is IMPORTANT that the threads are engaged to obtain the ultimate strength of the anchorage. If the original threaded anchors are 7/16" UNF, the supplied eye-bolts can be used. Carefully inspect the metal around the anchorages both inside the cockpit and from underneath. If there is any, this must be addressed by a professional before the belts are installed.

**If there are no original seat belt anchors, take this project to a professional mechanic or body shop with experience working on classic cars.**



### **Moss Motors, Ltd.**

440 Rutherford Street, Goleta, California 93117  
In the US & Canada Toll Free (800) 667-7872 FAX (805) 692-2510 (805) 681-3400

### **Moss Europe Ltd.**

Hampton Farm Industrial Estate, Hampton Road West, Hanworth Middlesex, TW13 6DB  
In the UK: 020-8867-2020 FAX:- 020-8867-2030