



## Dynolite NN Gear Oil 85W-140

### No Noise EP Gear Oil for Hypoid Gears

A high performance gear oil formulated using the latest sulphur-phosphorus technology, which assures excellent protection of the gears against metal-to-metal contact under the most severe conditions, even under shock-loads. This specially formulated oil was developed to mask noisy gearboxes and gears and is compatible with bronze, copper & brass components. Please Note: this oil will mask the noise but does not prolong the life of a worn out mechanical component.

### Features & Benefits

#### Superior oxidation and thermal stability

This oil shows a superior oxidation and thermal stability and has a good resistance against foaming. Even at higher temperatures an effective lubricating film thickness assures proper lubrication.

#### Excellent Resistance to Wear

Provides a superior level of protection in heavy duty applications, where shock load conditions can be extreme. The additive technology provides maximum protection against wear and corrosion, maintaining the life of critical components.

### Key Applications

- Heavy duty non-synchronized manual transmissions, axles and final drives where API GL-5 quality oils are specified.
- Other Gearboxes like high speed/shock load, high speed/low torque and/or low speed/high torque.
- Please visit our website for applications guide and more details.

### Approvals or Performance

- API : GL-5

### Technical Characteristics

SAE viscosity grade	85W-140
Density (20°C), g/cm <sup>3</sup>	0.903
Flash point (COC), °C	224
Kinematic viscosity (40°C), mm <sup>2</sup> /s (100°C), mm <sup>2</sup> /s	356.80 25.70
Viscosity index	95
Pour point, °C	-16.0

### Health & Safety

This Dynolite lubricant is unlikely to present any significant health or safety hazard when properly used in the recommended application, and good standards of industrial and personal hygiene are maintained. For further guidance on Product Health & Safety refer to the appropriate Dynolite Safety Data Sheet.

### Protect the environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

Available sizes - 1 litre (GGL823310).